

## **Gasoline Tuning Chart**

## Sunoco to Rockett Brand®

Sunoco Product / S. G. Leaded Products	Rockett Brand® / S. G.	<u>Tuning Suggestions</u>
Sunoco Standard 110 / 0.729	Rockett 110 / 0.710	Richen Mixture by 2 Jet Sizes
Sunoco Supreme 112 / 0.715	Rockett 112 / 0.721	No Change
Sunoco HCR Plus 114 / 0.739	Rockett 114 / 0.727	Richen Mixture by 1 Jet Size
Sunoco Maximal 116 / 0.708	Rockett 118 / 0.701	Richen Mixture by 1 Jet Size
Sunoco Max N.O.S. 116 / 0.731	Rockett 118 / 0.701	Richen Mixture by 3 Jet Sizes
Unleaded Products		
Sunoco GT 100 Unleaded 100 / 0.768	Rockett 100 Unleaded / 0.717	Richen Mixture by 4 Jet Sizes
Sunoco GT Plus Unleaded 104 / 0.762	Rockett 100 Unleaded / 0.717	Richen Mixture by 3 Jet Sizes

Note: When increasing the jet size in a Holley carburetor from #91 to #92, the area of the jet opening is increased by approximately 2.2%, and the mixture is theoretically richened by a similar amount. Be sure to check your results.

## WHEN IN DOUBT, GO RICHER

For more information or your nearest Rockett™ Brand Distributor, call or click: 1-800-345-0076 / www.rockettbrand.com